

AQUAWASH

www.aquawash.co.uk

Tel: 0141 881 3333



Aquawash DD18/200 12.5hp Twin Cylinder Kubota Diesel Engine Driven Hot & Cold Trailer Unit complete with 2 x Interlinked 300 Litre Baffled Polyethylene Tanks

Trailer Specification

- Heavy Duty Galvanised Chassis
- 2 x Interlinked 300L Baffled Polyethylene Water Tanks
- Fast Drain Valve
- 1800Kg Rated Running Gear
- Lockable Tow Hitch
- Lighting Board to EEC Specification
- HD Galvanised Hose Reel with Stainless Steel Shaft
- Dimensions 302cm (L) x 187cm (W) x 173cm (H)
- Weight Unladen – 800Kgs
- Weight Laden – 1550Kgs
- 50 Litre Chemical Storage
- Supplied with Spare Wheel

Machine Specification

- Kubota Z482 Twin Cylinder 12.5hp Water Cooled Continually Rated Diesel Engine
- Positive Displacement HAWK Plunger Pump
- 3000 PSI at 18 Litres Per Minute
- Double Wound Vertical Heating Coil
- Engine & Water Heater Coil independently mounted on anti-vibration pads
- Purpose Built 110V Generator
- Triple V Belt Drive – Single Screw Adjustment
- Low Pressure Steam Stage
- Low Pressure Detergent Injection
- 70 Litre Diesel Capacity